

Glutolin MT Fabric Adhesive

Ready to use, solvent-free dispersion adhesive for glass fibre fabric wallpapers.

Instructions for use:	<i>Glutolin MT</i> is suitable for pasting lined and unlined glass fibre fabrics as well as for heavy textile and vinyl wallpapers.	
Technical specifications:	Components:	Polyvinyl acetate ethylene dispersion
	pH-value:	ca. 9
	Density:	ca. 1.03 g/cm ³
	Usage:	200-300 g/m ²
Surface preparation:	The surface must be dry, firm, dust and grease-free. Remove old, peeling wallpapers and paint coats using <i>Glutolin TA Wallpaper Remover</i> . Make good cracks and holes using <i>Glutofill WF Filler</i> or <i>Glutifill WG Super Bonding Filler</i> . Pretreat highly absorbent, sanding or chalking surfaces with <i>Glutogrund LF Deeply Penetrating Primer – Solvent Free</i> .	
Application:	Apply <i>Glutolin MT</i> to the surface in wallpaper strip widths using a roller or brush, place the cut glass fibre fabric in the moist adhesive bed and uniformly press on the fabric. Do not paint over the fabric until the adhesive has completely dried. Observe the pasting recommendations of the fabric manufacturer. Immediately remove any adhesive residues with a damp cloth. Clean tools in water immediately after use. Do not use if the surface and/or room temperature is less than +5° Celsius.	
Storage:	Store in a cool place! Keep containers tightly sealed! The adhesive is frost-resistant. If frozen, defrost in room temperature and stir before use.	
Important information:	Please see the EU Safety Data Sheet for all safety -related data (EU-CLP)	
Available sizes:	3 kg bucket Art. no 001752074 5 kg bucket Art. no 001713074 18 kg bucket Art. no 001715074	